

## Wicked Skulls – Decal Application Instructions

All of WickedSkulls Decals are Custom Designed Artwork by Michael Spano of [SkullsbySpano.com](http://SkullsbySpano.com) made Exclusively for Wicked Skulls.

They are copyrighted designs and cannot be reproduced without written permission from [CyberArt Studios](http://CyberArt Studios) and [WickedSkulls](http://WickedSkulls)

WickedSkulls Decals are a Full Color Digitally Printed - Hi-quality Laminated Vinyl Decal.

### Decal Description:

- Decal - Digitally printed with UV resistant solvent inks on white vinyl
- **Made in the USA - Made to last!**
- Die cut to the exact contour of the design.
- This is a simple "Peel-n-Stick" type decal.
- The decal can be applied to any clean smooth wax-free surface such as glass, metal, plastic, and fiberglass. Do not apply to hot items such as engine parts.
- The decal can be applied to: Helmets, Skate Boards, Vehicles, Trailers, Tool boxes, Motorcycles.
- A Urethane clear coat can be applied over the decal material, *\*\*but we do not guarantee your results.*
- Made of Professional Grade - Vehicle Wrap Vinyl – **Laminated for Extra Durability**

For smaller size Wicked Skulls decals we recommend a dry application. For our large decals, we recommend a wet application method. Below you will find instructions for both types of applications.

#### Dry Application

1. Clean the surface where you will apply the decal. Use window cleaner, soapy water or rubbing alcohol to prep the surface, and dry with a lint free cloth. Surface temperature should be 55F to 75F, and not in direct sunlight.
2. With clean dry hands, peel the sticker from the backing sheet. Try to handle the decal as little as possible, only holding by edges.
3. Line up the sticker how you would like it. Attach the bottom part of the sticker to the surface, using a squeegee or credit card wrapped in paper towel; rub the rest of the decal onto the surface.
4. If you do have any air bubbles trapped, use a pin to make a small hole and rub until all bubbles are out.

#### Wet Application

1. Clean the surface where you will apply the decal. Use window cleaner, soapy water or rubbing alcohol to prep the surface, and dry with a lint free cloth. Surface temperature should be 55F to 80F, and not in direct sunlight.
2. Get a spray bottle, fill with water and add two to three drops of dish washing detergent, shake bottle to mix solution. Spray a light mist of the fluid on the desired location where you will apply the decal.
3. Position the decal in the misted desired location, using a squeegee or credit card wrapped in paper towel, rub the decal from the center out pushing out any trapped fluid and air bubbles.